



Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications														Standard Accessories - Single Installation																				
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter
FourStroke																																			
F225 L	L			x	x	x	x	x	x	x	x		EFI	1,85:1		3.400	V6	5200-6000	216	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F225 XL	XL			x	x	x	x	x	x	x	x		EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F225 CXL	XL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F225 XXL	XXL			x	x	x	x	x	x	x	x		EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F225 CXXL	XXL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F250 XL	XL			x	x	x	x	x	x	x			EFI	1,75:1		4.600	V8	5200-6000	239	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F250 CXL	XL	x		x	x	x	x	x	x	x			EFI	1,75:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F300 XL	XL			x	x	x	x	x	x	x			EFI	1,75:1		4.600	V8	5200-6000	239	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F300 CXL	XL	x		x	x	x	x	x	x	x			EFI	1,75:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4
Verado																																			
F250 L Verado	L			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000	272	-	-	-	x	-	-	-	x	x	x	x	x	x	-	Revolution4	
F250 XL Verado	XL			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	x	-	Revolution4	
F250 CXL Verado	XL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F250 XXL Verado	XXL			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F250 CXXL Verado	XXL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F300 L Verado	L			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000	272	-	-	-	x	-	-	-	x	x	x	x	x	x	-	Revolution4	
F300 CL Verado	L	x		x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F300 XL Verado	XL			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F300 CXL Verado	XL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F300 XXL Verado	XXL			x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F300 CXXL Verado	XXL	x		x	x	x	x	x	x	x	x		EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	Revolution4		
F350 L Verado	L			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400	316	-	-	-	x	-	-	-	x	x	x	x	x	x	-	RevolutionX	
F350 CL Verado	L	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 XL Verado	XL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 CXL Verado	XL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 XXL Verado	XXL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 CXXL Verado	XXL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 XXXL Verado	XXXL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F350 CXXXL Verado	XXXL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 L Verado	L			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400	316	-	-	-	x	-	-	-	x	x	x	x	x	x	-	RevolutionX	
F400 CL Verado	L	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 XL Verado	XL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 CXL Verado	XL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 XXL Verado	XXL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 CXXL Verado	XXL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 XXXL Verado	XXXL			x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F400 CXXXL Verado	XXXL	x		x	x	x	x	x	x	x	x		EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	RevolutionX		
F600 L Verado	L	x		x	x	x	x	x	x	x	x		EFI	2,50:1		7.600	V12	5600-6400	572	-	-	-	x	-	-	-	VV 903 included		x	x	x	-	Verado12		
F600 XL Verado	XL	x		x	x	x	x	x	x	x	x		EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included		x	x	x	-	Verado12		
F600 XXL Verado	XXL	x		x	x	x	x	x	x	x	x		EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included		x	x	x	-	Verado12		
F600 XXXL Verado	XXXL	x		x	x	x	x	x	x	x	x		EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included		x	x	x	-	Verado12		

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																		Standard Accessories - Single Installation																		
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrCraft	SC100 Fuel Gauge SamrCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller	
Pro XS																																					
F115 L Pro XS	L			x	x		x		x					EFI	2,07:1		2.064	4	5300-600	163	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax	
F115 XL Pro XS	XL			x	x		x		x					EFI	2,07:1		2.064	4	5300-6300		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax	
F115 L Pro XS CT	L			x	x		x		x					EFI	2,38:1	x	2.064	4	5300-6300	165	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax	
F115 XL Pro XS CT	XL			x	x		x		x					EFI	2,38:1	x	2.064	4	5300-6300		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax	
F150 L Pro XS	L			x	x		x		x					EFI	2,08:1		3.000	4	5200-6000	207	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F150 XL Pro XS	XL			x	x		x		x					EFI	2,08:1		3.000	4	5200-6000		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F175 L Pro XS MTS	L			x	x		x		x	x				EFI	1,85:1		3.400	V6	5400-6000	213	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F175 XL Pro XS MTS	XL			x	x		x		x	x				EFI	1,85:1		3.400	V6	5400-6000		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F200 XL Pro XS	XL			x		x	x		x	x				EFI	1,85:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F200 L Pro XS TM DTS	L			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F200 L Pro XS TM MTS	L			x	x		x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F225 XL Pro XS	XL			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F225 L Pro XS TM DTS	L			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F250 XL Pro XS	XL			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F250 CXL Pro XS	XL	x		x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F250 L Pro XS TM DTS	L			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F300 XL Pro XS	XL			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F300 CXL Pro XS	XL	x		x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	
F300 L Pro XS TM DTS	L			x		x	x		x	x				EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4	

* Dry weight is for the lightest model and excludes engine oil, rigging, and propeller.

Dual Installations of FourStroke engines 115 HP up to 150 HP include the following instruments: 2x SC1000 Tacho, 1x SC1000 Speedo, 2x SC100 Trim Gauge, 1x VesselView Mobile

Dual Installations of FourStroke, Verado and Pro XS engines 175 HP up to 400 HP include the following instruments: 2x SC1000 Tacho, 1x SC1000 Speedo, 2x SC100 Trim Gauge, 1x SC100 Fuel Gauge, 1x VesselView Mobile

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																		Standard Accessories - Single Installation																			
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller		
SeaPro																																						
F350 XL SeaPro	XL			x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900	316	-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	-	RevolutionX
F350 CXL SeaPro	XL	x		x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	-	RevolutionX
F350 XXL SeaPro	XXL			x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	-	RevolutionX
F350 CXXL SeaPro	XXL	x		x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	-	RevolutionX
F350 XXXL SeaPro	XXXL			x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	-	RevolutionX
F350 CXXXL SeaPro	XXXL	x		x		x		x		x				EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	-	RevolutionX	
F500 L SeaPro	L	x		x		x		x		x				EFI	2,50:1		7.600	V12	5000-5800	572	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	Verado12	
F500 XL SeaPro	XL	x		x		x		x		x				EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	Verado12
F500 XXL SeaPro	XXL	x		x		x		x		x				EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	Verado12
F500 XXXL SeaPro	XXXL	x		x		x		x		x				EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	Verado12

* Dry weight is for the lightest model and excludes engine oil, rigging, and propeller.

** SeaPro Engines are shipped with SmartCraft Instruments with black face

Dual Installations of SeaPro engines 115 HP up to 300 HP include the following instruments: 2x SC1000 Tacho, 2x SC100 Trim Gauge, 1x SC100 Fuel Gauge, 1x VesselView Mobile